

| Model No. | Insulation Color | Wire Range mm2/Awg 适用  | Tab Size 插片             | Dimension(mm/inch)主要尺寸                                                           | Packing 包 |
|-----------|------------------|------------------------|-------------------------|----------------------------------------------------------------------------------|-----------|
| 631285    | Red              | 0.5-1.5mm2<br>22-16AWG | .020*.110<br>(0.5*2.8)  | 2.8(.110)/6.5(.256)/19.5<br>(.756)/10.0(.394)/3.6<br>(.141)/1.7(.066)/0.5(.020)  | 1000/500  |
| 631288    | Red              | 0.5-1.5mm2<br>22-16AWG | .032*.110<br>(0.8*2.8)  | 2.8(.110)/6.5(.256)/20.5<br>(.807)/10.0(.394)/3.6<br>(.141)/1.7(.066)/0.4(.016)  | 1000/500  |
| 631485    | Red              | 0.5-1.5mm2<br>22-16AWG | .020*.187<br>(0.5*4.75) | 4.75(.187)/6.5(.256)/19.5<br>(.756)/10.0(.394)/3.6<br>(.141)/1.7(.066)/0.5(.020) | 1000/500  |
| 631488    | Red              | 0.5-1.5mm2<br>22-16AWG | .032*.187<br>(0.8*4.75) | 4.75(.187)/6.5(.256)/20.5<br>(.807)/10.0(.394)/3.6<br>(.141)/1.7(.066)/0.4(.016) | 1000/500  |
| 631638    | Red              | 0.5-1.5mm2<br>22-16AWG | .032*.250<br>(0.8*6.35) | 6.35(.250)/7.7(.303)/21.0<br>(.826)/10.0(.394)/3.6<br>(.141)/1.7(.066)/0.4(.016) | 1000/500  |
| 635485    | Blue             | 1.5-2.5mm2<br>16-14AWG | .020*.187<br>(0.5*4.75) | 4.75(.187)/6.5(.256)/19.0<br>(.748)/10.0(.394)/4.0<br>(.157)/2.3(.091)/0.5(.020) | 1000/500  |
| 635488    | Blue             | 1.5-2.5mm2<br>16-14AWG | .032*.187<br>(0.8*4.75) | 4.75(.187)/6.7(.267)/21.0<br>(.826)/10.0(.394)/4.0<br>(.157)/2.3(.091)/0.4(.016) | 1000/500  |
| 635638    | Blue             | 1.5-2.5mm2<br>16-14AWG | .032*.250<br>(0.8*6.35) | 6.35(.250)/7.7(.303)/21.0<br>(.826)/10.0(.394)/4.0<br>(.157)/2.3(.091)/0.4(.016) | 1000/500  |
| 633485    | Yellow           | 4-6mm2 12-<br>10AWG    | .020*.187<br>(0.5*4.75) | 4.75(.187)/7.7(.303)/25.0<br>(.984)/13.0(.511)/6.0<br>(.236)/3.5(.137)/0.5(.020) | 1000/500  |
| 633488    | Yellow           | 4-6mm2 12-<br>10AWG    | .032*.187<br>(0.8*4.75) | 4.75(.187)/7.7(.303)/25.0<br>(.984)/13.0(.511)/6.0<br>(.236)/3.5(.137)/0.4(.016) | 1000/500  |
| 633638    | Yellow           | 4-6mm2 12-<br>10AWG    | .032*.250<br>(0.8*6.35) | 6.35(.250)/7.7(.303)/25.0<br>(.984)/13.0(.511)/6.0<br>(.236)/3.5(.137)/0.4(.016) | 1000/500  |